



MATERIAL SAFETY DATA SHEET

Leisure Time Spa Down

1. Product And Company Identification	
<u>Supplier</u> Leisure Time 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com	<u>Manufacturer</u> Advantis Technologies Inc. 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com
<u>Supplier Emergency Contacts & Phone Number</u> CHEMTREC - DAY OR NIGHT: (800) 424-9300	<u>Manufacturer Emergency Contacts & Phone Number</u> CHEMTREC - DAY OR NIGHT: (800) 424-9300
Issue Date: 04/17/2001 Product Name: Leisure Time Spa Down CAS Number: Not Established Chemical Family: pH reducer Chemical Formula: Proprietary Mixture MSDS Number: 23	

2. Composition/Information On Ingredients			
	Ingredient Name	CAS Number	Percent Of Total Weight
	SODIUM BISULFATE	7681-38-1	
Ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. Materials determined to be health hazards are listed if they comprise 1% or more of the composition. Materials identified as carcinogens are listed if they comprise 0.1% or more of the composition. Information on proprietary materials is available in 29CFR 1910.1200(i)(1).			

Hazards Identification (Pictograms)

3. Hazards Identification <u>Primary Routes(s) Of Entry</u> Skin Contact <u>Eye Hazards</u> Causes eye irritation. <u>Skin Hazards</u> Causes skin irritation. <u>Ingestion Hazards</u> Harmful if swallowed. <u>Inhalation Hazards</u> Causes respiratory tract irritation.
--

MATERIAL SAFETY DATA SHEET

Leisure Time Spa Down

3. Hazards Identification - Continued

Signs And Symptoms

Irritation of Eyes, Skin and Respiratory Passages

First Aid (Pictograms)



4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a physician or a poison control center immediately.

Skin

In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes.

Ingestion

DO NOT INDUCE VOMITING. Call a physician or a poison control center immediately. If victim is fully conscious, give one or two cups of water or milk to drink.

Inhalation

If breathing is difficult, give oxygen. If inhaled, remove to fresh air.

Fire Fighting (Pictograms)



5. Fire Fighting Measures

Flash Point: N/A °F

Fire And Explosion Hazards

At temperatures in excess of 570 F, hazardous fumes of sulfur dioxide and sulfur trioxide are evolved. Use forced draft ventilation or gas mask.

Extinguishing Media

Use the appropriate extinguishing media for the surrounding fire.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material.

6. Accidental Release Measures

Clean up spill immediately. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Neutralize spill area with soda ash or lime. Flush spill area with water. Use appropriate containers to avoid environmental contamination.

MATERIAL SAFETY DATA SHEET

Leisure Time Spa Down

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store material in a cool and dry place. Keep containers tightly closed.

Handling Precautions

Use only with adequate personal protection.

Storage Precautions

Store in a cool dry place.

Work/Hygienic Practices

Use safe chemical handling procedures suitable for the hazards presented by this material. Avoid contact with eyes. Solutions of this material are acidic and strongly irritating. Will attack most metals.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls

Local exhaust acceptable. Special exhaust not required

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

None normally required.

9. Physical And Chemical Properties

Appearance

Off white granular powder

Odor

Bland odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: 350 °F

Specific Gravity: n/a

Molecular Weight: NOT DETERMINED

Percent Volitales: NOT DETERMINED

Packing Density: 83 lb/cu.ft

Vapor Pressure: NOT DETERMINED

Solubility: SOLUBLE

MATERIAL SAFETY DATA SHEET

Leisure Time Spa Down

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products

At Temperatures in excess of 570F Hazardous fumes of Sulfur Dioxide and Sulfur Trioxide are evolved.

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Proper Shipping Name

NOT REGULATED

Hazard Class

NOT REGULATED

DOT Identification Number

NONE

DOT Shipping Label

NOT ASSIGNED

Packaging Requirements

NOT ASSIGNED

15. Regulatory Information

Ingredient(s) - State Regulations

SODIUM BISULFATE

New Jersey - Workplace Hazard

New Jersey - Special Hazard

New York City - Hazardous Substance

NFPA



HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	1
PERSONAL PROTECTION	C

16. Other Information

Revision/Preparer Information

MSDS Preparer: JHW3

This MSDS Superceeds A Previous MSDS Dated: 07/18/2000

MATERIAL SAFETY DATA SHEET

Leisure Time Spa Down

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Leisure Time

Printed Using MSDS Generator™ 2000